
Basic:1.0 Device Definition Version 1.0

For UPnP™ Version 1.0

Status: Template Design Complete

Date: 2002-12-12

This Standardized DCP has been adopted as a Standardized DCP by the Steering Committee of the UPnP™ Forum, pursuant to Section 2.1(c)(ii) of the UPnP™ Forum Membership Agreement. UPnP™ Forum Members have rights and licenses defined by Section 3 of the UPnP™ Forum Membership Agreement to use and reproduce the Standardized DCP in UPnP™ Compliant Devices. All such use is subject to all of the provisions of the UPnP™ Forum Membership Agreement.

THE UPNP™ FORUM TAKES NO POSITION AS TO WHETHER ANY INTELLECTUAL PROPERTY RIGHTS EXIST IN THE STANDARDIZED DCPS. THE STANDARDIZED DCPS ARE PROVIDED "AS IS" AND "WITH ALL FAULTS". THE UPNP™ FORUM MAKES NO WARRANTIES, EXPRESS, IMPLIED, STATUTORY, OR OTHERWISE WITH RESPECT TO THE STANDARDIZED DCPS, INCLUDING BUT NOT LIMITED TO ALL IMPLIED WARRANTIES OF MERCHANTABILITY, NON-INFRINGEMENT AND FITNESS FOR A PARTICULAR PURPOSE, OF REASONABLE CARE OR WORKMANLIKE EFFORT, OR RESULTS OR OF LACK OF NEGLIGENCE.

© 2002 Contributing Members of the UPnP™ Forum. All Rights Reserved.

Authors	Company
Scott Lawrence	GlobespanVirata

Contents

1. OVERVIEW AND SCOPE.....	3
CHANGE LOG	3
2. DEVICE DEFINITIONS	4
DEVICE TYPE.....	4
DEVICE MODEL	4
THEORY OF OPERATION	4
3. XML DEVICE DESCRIPTION.....	4
4. TEST.....	3

List of Tables

Table 1: Device Requirements	4
------------------------------------	---

1. Overview and Scope

This device template is compliant with the UPnP Architecture, Version *1.0*.

Basic:1.0 provides a mechanism for products that wish to use UPnP, but for which there is not yet an appropriate standard base device type. The Basic Device type does not define any Services or embedded Devices, although a particular product may incorporate elements defined by other UPnP Standards and/or vendor-defined extension types.

A minimal Basic Device (one that does not add any services or embedded devices) is discoverable using UPnP discovery and may provide identifying information and a Presentation URL using the normal Device Description mechanism.

The Basic Device type also may be useful as the root device type for a product that incorporates standard elements in ways not anticipated by the standard types. For example, a television that also includes room light controls and a printer might choose to use the Basic Device type as the root type, with embedded devices and services chosen from the appropriate standard types.

Note: This definition relies on an Architecture change under consideration in the UPnP Forum Technical Committee: that the definition of the ‘servicelist’ element be changed to include ‘minoccurs=”0”’; that is, that it be made an optional element.

Change Log

- 0.8 Initial Creation
- 0.9 Editorial improvements; no functional changes.
- 0.10 Voted Template Design Complete
- 0.11 Added non-normative Appendix A to explain why no service is defined for this DCP.
- 0.12 Updated to version 1.0

2. Device Definitions

Device Type

The following device type identifies a device that is compliant with this template:

urn:schemas-upnp-org:device:Basic:1.0

Device Model

Products that expose devices of the type **urn:schemas-upnp-org:device:Basic:1.0** do not require the implementation of any embedded device or service type.

Table 1: Device Requirements

DeviceType	Root	Req. or Opt. ¹	ServiceType	Req. or Opt. ¹	Service ID ²
Basic:1.0	Root				

¹ R = Required, O = Optional, X = Non-standard.

² Prefixed by urn:[upnp-org:serviceId](#):

Theory of Operation

The Basic Device does not define any Service Actions or Evented State Variables, so there are no operations on it that Control Points would use. For a discussion of the rationale for the absence of services for the Basic Device, see Appendix A.

3. XML Device Description

```
<?xml version="1.0"?>
<root xmlns="urn:schemas-upnp-org:device-1-0">
  <specVersion>
    <majormajorminorminor>
  </specVersion>
  <URLBase>base URL for all relative URLs</URLBase>
  <device>
    <deviceType>urn:schemas-upnp-org:device:Basic:1</deviceType>
    <friendlyName>short user-friendly title</friendlyName>
    <manufacturer>manufacturer name</manufacturer>
    <manufacturerURL>URL to manufacturer site</manufacturerURL>
    <modelDescription>long user-friendly title</modelDescription>
    <modelName>model name</modelName>
    <modelNumber>model number</modelNumber>
    <modelURL>URL to model site</modelURL>
    <serialNumber>manufacturer's serial number</serialNumber>
    <UDN>uuid:UUID</UDN>
    <UPC>Universal Product Code</UPC>
    <iconList>
      <icon>
```

```
<mimetype>image/format</mimetype>
<width>horizontal pixels</width>
<height>vertical pixels</height>
<depth>color depth</depth>
<url>URL to icon</url>
</icon>
XML to declare other icons, if any, go here
</iconList>
<presentationURL>URL for presentation</presentationURL>
</device>
</root>
```

4. Test

A Basic Device that does not extend the type as specified in this document needs to pass only the addressing, discovery and description phases of the UPnP Certification test.

Appendix A. Services in a Basic Device

This appendix is included to explain reasons why no standard Service types are included for the Basic Device; it is not a normative part of the Basic Device specification.

The Basic Device Type does not specify any services. The UPnP Forum Technical Committee has amended the UPnP Device Architecture to make the serviceList element in the device description optional, and to permit it to be empty, so this is now permitted.

The rationale for not requiring a service in the definition of a Basic Device is this:

- A device that implements the Basic Device should have access to any Intellectual Property needed to implement UPnP.
- Use of any UPnP Forum Member Intellectual Property is governed by the UPnP Forum Member Agreement, which refers to Standard DCPs, but is mute regarding Services.
- A device that does not contain any Standard Services should not get the UPnP logo (because the meaning of the logo is that the device _does_ contain one or more Standard Services - so the consumer can reasonably expect that it will work with other devices and control points appropriate to its type). Allowing a device with no Standard Services to use the logo would dilute the value of the logo.
- Use of the logo is granted by the UPnP Implementors Corp. (UIC) Member Agreement, which requires that in order to use the UPnP logo, the device must be certified by the UIC as having at least one Standard Service.

By not requiring a Standard Service in the Basic Device, we allow a product to meet the Intellectual Property requirement without also creating a right of that product to use the logo.

Because the UPnP Device Architecture allows arbitrary services in any device type, a product using the Basic Device type may incorporate services.

There do exist Control Points which enforce the old requirement that a device contain at least one service. In order to satisfy such CPs, a product may want to add either a 'null' service that has no actions or evented state variables, or one that actually does something - standard or vendor-defined.

If a Basic Device does include a Standard Service, then it could get rights to the logo on that basis. This covers the case of a device that is not obviously of a standard type, but can be used in some standard way, such as a UPnP Birdcage (no standard device type, so it would use Basic) that has a built-in video camera so that you can check on Tweetie remotely (a standard media source service).